


P.C.B. LAYOUT

MATERIALS:

1. Housing: PBT (UL 94V-0), Blue / Black
2. Contacts: Brass
3. Shell: SPCC
4. Rivet: Copper Alloy(Lead $\leq$ 40000PPM)
5. Board Lock: SPCC
6. Screw: SPCC



Or Copper Alloy(Lead $\leq$ 40000PPM)

FINISH:


1. Contacts: Gold Flash Plated on Contact Area
Tin Plated on Solderails
Nickel Under Plated Over All
2. Shell: Nickel Plated
3. Rivet: Nickel Plated
4. Board Lock: Tin Plated
5. Screw: Nickel Plated

SPECIFICATION:


1. Current Rating: 2 Amp
2. Dielectric Withstanding Voltage: AC 500V For 1 minute
3. Insulation Resistance: 5000M Ω Min
4. Contact Resistance: 30m Ω Max.
5. Operating Temperature: -55°C to +105°C



鉗合型



鉗合鎖螺絲型



僅供參考

KIN TA PRECISION CO., LTD.
金泰精密有限公司

TITLE / 品名: VGA 90度 15母 (板邊距5.08) Dip Type

核準發行章

PART NO / 料號: D2210-15F-Rxxxx

APPROVE / 核準	CHECKED / 審查	DRAWING / 繪圖	DRAWING NO / 圖號
Kin	Chenrong	Chenrong	K-0D-014-00

UNIT / 單位	SHEET 1 OF 1
mm	

NO.	REV / 版本	修訂內容	日期
	1.0	圖面僅供參考, 實際尺寸以承認圖為主	2025/12/19