




P.C.B. LAYOUT


MATERIALS:
1. Housing: PBT (UL94 V-0), Black
2. Contacts: Brass
3. Shell: SPCC
4. Back Screws: Copper Alloy(Lead $\leq$ 40000PPM)
5. Screw: SPCC
Or Copper Alloy(Lead $\leq$ 40000PPM)

FINISH:
1. Contacts: Gold Flash Plated on Contact Area
Tin Plated on Solderails
Nickel Under Plated Over All
2. Shell: Nickel Plated
3. Back Screws: Nickel Plated
4. Screw: Nickel Plated


SPECIFICATION:
1. Current Rating: 2 Amp
2. Dielectric Withstanding Voltage: AC 500V r.m.s.
3. Insulation Resistance: 5000M Ω Min. at DC 500V
4. Contact Resistance: 30m Ω Max.
5. Operating Temperature: -55°C to 105°C



鉚合型



鉚合鎖螺絲型



NO. OF POS.	A	B	C	D	E	F
15	30.80	24.99	16.92	19.10	2.29	10.50
26	39.20	33.32	25.25	27.60	2.29	10.70
44	53.10	47.04	38.96	41.10	2.29	10.70
62	69.40	63.50	55.50	57.45	2.41	10.70

僅供參考

KIN TA PRECISION CO., LTD.
金泰精密有限公司

TITLE / 品名: D-Sub 180度 三排 公座 Dip Type (鐵殼兩側鉚下方銅柱H=6.0)

核准發行章

PART NO / 料號: D91240-xxM-Rxxxx

APPROVE / 核准	CHECKED / 審查	DRAWING / 繪圖	DRAWING NO / 圖號	UNIT / 單位	NO. OF POS.
Kin	Chenrong	Chenrong	K-0D-034-00	mm	1

UNIT / 單位	NO. OF POS.
mm	1

NO.	REV / 版本	修訂內容	日期
1.0		圖面僅供參考, 實際尺寸以承認圖為主	2025/12/19