




MATERIALS:

- 1. Housing: PBT (UL94 V-0), Black
- 2. Contacts: Brass
- 3. Shell: SPCC

FINISH:


- 1. Contacts: Gold Flash Plated on Contact Area
Tin Plated on Solderails
Nickel Under Plated Over All
- 2. Shell: Nickel Plated

SPECIFICATION:

- 1. Current Rating: 2 Amp
- 2. Dielectric Withstanding Voltage: AC 500V r.m.s.
- 3. Insulation Resistance: 5000MΩ Min. at DC 500V
- 4. Contact Resistance: 30mΩ Max.
- 5. Operating Temperature: -55°C to 105°C

僅供參考

NO. OF POS.	A	B	C	D	E	F
15	30.80	24.99	16.33	19.10	2.29	10.50
26	39.20	33.32	24.80	27.60	2.29	10.70
44	53.10	47.04	38.38	41.10	2.29	10.70
62	69.40	63.50	54.80	57.45	2.41	10.70

KIN TA PRECISION CO., LTD. 金泰精密有限公司				TITLE / 品名: D-Sub 180度 三排 母座 Solder Type (標規/無銅柱)					核準發行章
PART NO / 料號: D92000-xxF-Rxxxx				  					
APPROVE / 核準	CHECKED / 審查	DRAWING / 繪圖	DRAWING NO / 圖號	UNIT / 單位	 				
<i>Kin</i>	<i>Chenrong</i>	<i>Chenrong</i>	K-0D-031-00	mm	SHEET 1 OF 1			1.0	
				NO.	REV / 版本	修訂內容		日期	